## NSN 5962-01-459-3195

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-459-3195

| Maximum Power Dissipation Rating:             |
|---|
| 700.0 milliwatts                              |
| Operating Tempurature Range:                  |
| -40.0/+85.0 degrees celsius                   |
| Storage Tempurature Range:                    |
| -65.0/+150.0 degrees celsius                  |
| End Application:                              |
| Sdv mod1 ds e/i fscm 53711                    |
| Features Provided:                            |
| Monolithic                                    |
| Inclosure Material:                           |
| Ceramic                                       |
| Inclosure Configuration:                      |
| Dual-in-line                                  |
| Output Logic Form:                            |
| Complementary-metal oxide-semiconductor logic |
| Design Function And Quantity:                 |
| 1 buffer, inverting                           |
| Terminal Surface Treatment:                   |
| Solder  |
| Product Name:                                 |
| Hex inverting buffer                          |
| Voltage Rating And Type Per Characteristic:   |
| -0.5 volts input and 18.0 volts input         |
| Terminal Type And Quantity:                   |
| 16 printed circuit                            |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |
| Yes - demil/mli                               |
| Fiig:   |
| A458a0  |
|   |
|   |