# NSN 5962-01-460-0466

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-460-0466

# **Body Length:**

Between 0.189 inches and 0.197 inches

# **Body Width:**

Between 0.150 inches and 0.157 inches

# **Body Height:**

Between 0.043 inches and 0.065 inches

# **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### End Application:

C-17 acft

#### Features Provided:

Electrostatic sensitive and bipolar and selected item

## Inclosure Material:

Plastic

## Inclosure Configuration:

Dual-in-line

Output Logic Form:

Bipolar metal-oxide semiconductor

## Design Function And Quantity:

1 reference, voltage, analog

## **Product Name:**

Microcircuit, linear, plastic encapsulated surface mount

## Voltage Rating And Type Per Characteristic:

10.0 volts output and 36.0 volts power source

## Memory Capacity:

None

## **Special Features:**

Used on 6625-01-443-0552 fscm=03950

## **Special Test Features:**

Upscreening consists of extended temperature range testing of pem to -55 to +55 degrees celsius

## **Test Data Document:**

89954-356a1407 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Terminal Type And Quantity:**

8 gullwing

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5962-01-460-0466

Digital Microcircuit - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0

