

View Online at <https://aerobasegroup.com/nsn/5962-01-460-9466>

**Maximum Power Dissipation Rating:**

1.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

1055-01-251-9756 e/i fscm 67268

**Features Provided:**

Low power and monolithic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, memory, digital, cmos, 128k x8 static random access memory (sram) low power, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

-0.5 volts input and 7.0 volts input

**Memory Device Type:**

Ram

**Special Features:**

Circuit function 128k x 8 standard power cmos sram dual ce / access time 20 ns

**Test Data Document:**

96906-mil-std-833 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

32 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0