

View Online at <https://aerobasegroup.com/nsn/5962-01-461-2352>

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Electrical e/i fscm 81349

**Features Provided:**

Bipolar and monolithic and w/common enable

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Design Function And Quantity:**

1 flip-flop, d-type

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, advanced bipolar cmos, octal edge-triggered d-type flip-flop with clock enable, ttl compatible inputs, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

-0.5 volts input and 7.0 volts input

**Special Features:**

Ttl compatible inputs

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0