## NSN 5962-01-462-1573

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-462-1573

| Maximum Power Dissipation Rating:   |
|---|
| 500.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| End Application:  |
| A/f-18dcn e/i fscm 93322  |
| Features Provided:  |
| W/differential outputs and monolithic   |
| Inclosure Configuration:  |
| Leaded chip carrier   |
| Design Function And Quantity:   |
| 1 receiver, line  |
| Terminal Surface Treatment:   |
| Solder  |
| Product Name:   |
| Ceramic chip carrier assembly, flat j-leaded  |
| Voltage Rating And Type Per Characteristic:   |
| 7.0 volts power source  |
| Special Features:   |
| Esd   |
| Test Data Document:   |
| 96906-mil-std-883  standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:   |
| 20 j-hook   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A458a0  |
|   |