NSN 5962-01-462-6102

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-462-6102

| Body Length: |
|--------------------------------------------------------------------------------------------------------------------|
| 0.350 inches |
| Body Width: |
| 0.350 inches |
| Body Height: |
| 0.100 inches |
| Maximum Power Dissipation Rating: |
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| MIvs cage 30003 |
| Features Provided: |
| Electrostatic sensitive and monolithic |
| Inclosure Material: |
| Silicon |
| Inclosure Configuration: |
| Leaded chip carrier |
| Design Function And Quantity: |
| 4 receiver, line |
| Case Outline Source And Designator: |
| C-2 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Microcircuit j leaded |
| Voltage Rating And Type Per Characteristic: |
| 30.0 volts power source |
| Special Features: |
| Altered 5962-86888022a by adding a j lead |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 20 j-hook |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

Yes - demil/mli

NSN 5962-01-462-6102

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

