NSN 5962-01-462-6615

Memory Microcircuit - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5962-01-462-6615

Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
303.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Safcs cage 26512
Features Provided:
Hermetically sealed and burn in and programmable and bipolar and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
16 input
Case Outline Source And Designator:
D-8 mil-m-38510
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit pal
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Memory Device Type:
Pal
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:

NSN 5962-01-462-6615

Memory Microcircuit - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0