NSN 5962-01-463-1477

Hybrid Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-463-1477

Maximum Power Dissipation Rating:
720.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
2320-01-123-1610 e/i fscm 67268
Features Provided:
Monolithic and hybrid and synchronous
Inclosure Configuration:
Dual-in-line
Design Function And Quantity:
1 converter, resolver to digital
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, hybrid, linear, 11.8 volt, synchro and resolver to digital converter
Voltage Rating And Type Per Characteristic:
-0.3 volts input and 7.0 volts input
Hybrid Technology Type:
Multichip
Special Features:
Circuit function - 11.8v, 400 hz/ r/d converter, 16 bit/accuracy - 1.3 minutes
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
36 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A458a0