NSN 5962-01-463-2513

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-463-2513

Body Length:
Between 1.064 inches and 1.086 inches
Body Width:
Between 0.110 inches and 0.160 inches
Body Height:
Between 1.064 inches and 1.086 inches
Maximum Power Dissipation Rating:
2.2 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
ENDI-TE-MNS-N143
Features Provided:
Burn in, mil-std-883, class b and compatible cmos and hybrid and burn in, mil-std-883, class b
Inclosure Configuration:
Pin grid array
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Design Function And Quantity:
1 memory, static ram
Terminal Surface Treatment:
Solder
Product Name:
Sram, 128k x 32-bit
Voltage Rating And Type Per Characteristic:
7.0 volts input
Hybrid Technology Type:
Monolithic
Special Features:
Hex-in-line, single cavity, w/stand-offs
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
66 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-463-2513

Hybrid Microcircuit - Page 2 of 2



Fiig:

A458a0