NSN 5962-01-463-2513

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-463-2513

Body Length:

Between 1.064 inches and 1.086 inches

Body Width:

Between 0.110 inches and 0.160 inches

Body Height:

Between 1.064 inches and 1.086 inches

Maximum Power Dissipation Rating:

2.2 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

ENDI-TE-MNS-N143

Features Provided:

Burn in, mil-std-883, class b and compatible cmos and hybrid and burn in, mil-std-883, class b

Inclosure Configuration:

Pin grid array

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Design Function And Quantity:

1 memory, static ram

Terminal Surface Treatment:

Solder

Product Name:

Sram, 128k x 32-bit

Voltage Rating And Type Per Characteristic:

7.0 volts input

Hybrid Technology Type:

Monolithic

Special Features:

Hex-in-line, single cavity, w/stand-offs

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

66 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-01-463-2513

Hybrid Microcircuit - Page 2 of 2

Fiig: A458a0

