

View Online at <https://aerobasegroup.com/nsn/5962-01-463-3687>

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

An/aar-44sim e/i fscm 67268

Features Provided:

Electrostatic sensitive and monolithic and burn in, mil-std-883, class d

Inclosure Configuration:

Pin grid array

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Design Function And Quantity:

1 memory, electrically erasable programmable rom

Terminal Surface Treatment:

Gold

Product Name:

Microcircuit, memory, digital, cmos 128k x 8 bit eeprom, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 6.0 volts input

Special Features:

Access time: 250 ns, write speed: 10ms, endurance: 10,000 cycle, software data protect: yes

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufacturer standards, etc.).

Terminal Type And Quantity:

36 case

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0