## NSN 5962-01-463-4515

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-463-4515

Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
1220-01-449-4179 e/i fscm 19200
Features Provided:
Monolithic and electrostatic sensitive
Inclosure Configuration:
Leadless flat pack
Product Name:
Microciruit 32k x 8 eeprom
Voltage Rating And Type Per Characteristic:
-0.3 volts input and 6.25 volts input
Memory Device Type:
Eeprom
Special Features:
Same as smd 5962-8863403yx except for the chip clear function which is not required
Supplementary Features:
Access time - 35ns/write speed - 10ms/write mode - byte/page/end of write indicator - data polling/toggle bit/endurance - 10, 000 cycles
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
32 leadless
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A458a0