

View Online at <https://aerobasegroup.com/nsn/5962-01-463-5171>

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Rsip, cage 67268

**Features Provided:**

3-state output and monolithic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Design Function And Quantity:**

8 transceiver

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, fast cmos octal bidirectional transceiver with three-state outputs, ttl compatible inputs and limited output voltage swing, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

-0.5 volts input and 7.0 volts input

**Special Features:**

Recommended operating supply (vcc) 4.5 to 5.5 vdc

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A458a0