NSN 5962-01-464-7917

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-464-7917 **Body Length:** 1.280 inches **Body Width:** 0.310 inches **Body Height:** 0.200 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** E-3a acft, rsip ppl **Features Provided:** Monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Design Function And Quantity:** 1 memory, programmable read only **Case Outline Source And Designator:** D-9 mil-m-38510 **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, digital, cmos, 2k x 8 one time programmable registered prom, monolithic silscon Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input **Special Features:** Recommended operating supply (vcc) 4.5 to 5.5 vdc; setup time 25 ns **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit

N/a **Unit Of Measure:**

Shelf Life:

NSN 5962-01-464-7917

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0