Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-465-3819

# Maximum Power Dissipation Rating:

500.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# **End Application:**

Alr-56c lot 2

### **Features Provided:**

Electrostatic sensitive

### **Inclosure Configuration:**

Dual-in-line

#### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

### **Design Function And Quantity:**

1 memory, erasable programmable

### Terminal Surface Treatment:

Solder

## **Product Name:**

Micocircuit, memory, digital, cmos, 262, 144-bit uv eraseable prom, monolithic silicon

# Voltage Rating And Type Per Characteristic:

-0.3 volts input and 6.5 volts input

**Special Features:** 

Circuit function: 32k x 8-bit uv eprom; access time: 150 ns

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### Terminal Type And Quantity:

28 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0