## NSN 5962-01-466-5223

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-466-5223 **Overall Width:** 0.870 inches **Body Length:** 0.280 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.045 inches and 0.090 inches **Maximum Power Dissipation Rating:** 675.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** C-17a acft **Features Provided:** Monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Design Function And Quantity:** 1 monitor, voltage **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, linear, supply voltage supervisors, monolithic silicon **Voltage Rating And Type Per Characteristic:** 3.6 volts input and 18.0 volts input **Special Features:** Case outline, mil-std-1835: gdfp1-f10 or cdfp2-f10; single svs for 5 volt systems w/pgmmable time delay **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5962-01-466-5223

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0