## NSN 5962-01-466-8940

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-466-8940

| Maximum Power Dissipation Rating:   |
|---|
| 180.0 milliwatts  |
| Operating Tempurature Range:  |
| -40.0/+85.0 degrees celsius   |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| End Application:  |
| General purpose electronic test equipment/end item is 6625-01-425-2551 analyer, spectrum  |
| Features Provided:  |
| Electrostatic sensitive and high speed and 3-state output   |
| Inclosure Material:   |
| Plastic   |
| Inclosure Configuration:  |
| Leaded chip carrier   |
| Output Logic Form:  |
| Complementary-metal oxide-semiconductor logic   |
| Design Function And Quantity:   |
| 1 flip-flop, d-type   |
| Terminal Surface Treatment:   |
| Solder  |
| Product Name:   |
| Octal d-type flip-flop with 3-state output/inverting  |
| Voltage Rating And Type Per Characteristic:   |
| -0.5 volts input and 7.0 volts input  |
| Terminal Type And Quantity:   |
| 20 gullwing   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A458a0  |
|   |
|   |
| Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input  Terminal Type And Quantity: 20 gullwing  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig: |