## NSN 5962-01-467-3110

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-467-3110

Storage Tempurature Range: -65.0/+150.0 degrees celsius Inclosure Configuration: Dual-in-line Design Function And Quantity: 1 control Current Rating Per Characteristic: 2.00 milliamperes collector cutoff current, dc, with specified resistance between base and em Product Name: Current mode pwm controller Voltage Rating And Type Per Characteristic: 2.5 volts input and 2.6 volts input Time Rating Per Chacteristic: 150.00 nanoseconds fall Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure:	
Inclosure Configuration:  Dual-in-line  Design Function And Quantity: 1 control  Current Rating Per Characteristic: 2.00 milliamperes collector cutoff current, dc, with specified resistance between base and em  Product Name:  Current mode pwm controller  Voltage Rating And Type Per Characteristic: 2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic: 150.00 nanoseconds fall  Terminal Type And Quantity: 8 pin  Shelf Life: N/a	
Dual-in-line  Design Function And Quantity:  1 control  Current Rating Per Characteristic:  2.00 milliamperes collector cutoff current, dc, with specified resistance between base and em  Product Name:  Current mode pwm controller  Voltage Rating And Type Per Characteristic:  2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic:  150.00 nanoseconds fall  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a	
Design Function And Quantity:  1 control  Current Rating Per Characteristic:  2.00 milliamperes collector cutoff current, dc, with specified resistance between base and em  Product Name:  Current mode pwm controller  Voltage Rating And Type Per Characteristic:  2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic:  150.00 nanoseconds fall  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a	
Current Rating Per Characteristic:  2.00 milliamperes collector cutoff current, dc, with specified resistance between base and em Product Name:  Current mode pwm controller  Voltage Rating And Type Per Characteristic:  2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic:  150.00 nanoseconds fall  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a	
Current Rating Per Characteristic:  2.00 milliamperes collector cutoff current, dc, with specified resistance between base and em Product Name:  Current mode pwm controller  Voltage Rating And Type Per Characteristic:  2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic:  150.00 nanoseconds fall  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a	
2.00 milliamperes collector cutoff current, dc, with specified resistance between base and em  Product Name:  Current mode pwm controller  Voltage Rating And Type Per Characteristic:  2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic:  150.00 nanoseconds fall  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a	
Product Name: Current mode pwm controller Voltage Rating And Type Per Characteristic: 2.5 volts input and 2.6 volts input Time Rating Per Chacteristic: 150.00 nanoseconds fall Terminal Type And Quantity: 8 pin Shelf Life: N/a	
Current mode pwm controller  Voltage Rating And Type Per Characteristic:  2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic:  150.00 nanoseconds fall  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a	ter
Voltage Rating And Type Per Characteristic:  2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic:  150.00 nanoseconds fall  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a	
2.5 volts input and 2.6 volts input  Time Rating Per Chacteristic:  150.00 nanoseconds fall  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a	
Time Rating Per Chacteristic: 150.00 nanoseconds fall  Terminal Type And Quantity: 8 pin  Shelf Life: N/a	
150.00 nanoseconds fall  Terminal Type And Quantity: 8 pin  Shelf Life: N/a	
Terminal Type And Quantity: 8 pin Shelf Life: N/a	
8 pin Shelf Life: N/a	
Shelf Life: N/a	
N/a	
Unit Of Measure:	
one of measure.	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	