NSN 5962-01-467-7643

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-467-7643

Body Length:
1.290 inches
Body Width:
0.310 inches
Body Height:
0.210 inches
Maximum Power Dissipation Rating:
1.2 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
2320-01-123-1610
Features Provided:
Monolithic and bipolar and programmable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
20 input
Design Function And Quantity:
1 array, logic
Current Rating Per Characteristic:
210.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
12.0 volts power source
Test Data Document:
81349-mil-prf-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
24 printed circuit
Specification Data:
81349-mil-prf-38510/505 government specification
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-01-467-7643

Digital Microcircuit - Page 2 of 2



em			

Yes - demil/mli

Fiig:

A458a0

Mil-std (military Standard):

Mil-prf-38510 spec.