NSN 5962-01-468-1705

Digital Microcircuit - Page 1 of 1



962-01-468-1705

View Online at https://aerobasegroup.com/nsn/59
Body Length:
Between 61.600 inches and 62.600 inches
Body Width:
Between 13.560 inches and 14.220 inches
Body Height:
4.060 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
997n-18adapt
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Design Function And Quantity:
4 receiver, asynchronous
4 receiver, asynchronous Terminal Surface Treatment:
Terminal Surface Treatment:
Terminal Surface Treatment: Solder
Terminal Surface Treatment: Solder Product Name:
Terminal Surface Treatment: Solder Product Name: Microcircuit, digital, uart
Terminal Surface Treatment: Solder Product Name: Microcircuit, digital, uart Voltage Rating And Type Per Characteristic:
Terminal Surface Treatment: Solder Product Name: Microcircuit, digital, uart Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input
Terminal Surface Treatment: Solder Product Name: Microcircuit, digital, uart Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Terminal Type And Quantity:
Terminal Surface Treatment: Solder Product Name: Microcircuit, digital, uart Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Terminal Type And Quantity: 48 printed circuit
Terminal Surface Treatment: Solder Product Name: Microcircuit, digital, uart Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Terminal Type And Quantity: 48 printed circuit Shelf Life:
Terminal Surface Treatment: Solder Product Name: Microcircuit, digital, uart Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Terminal Type And Quantity: 48 printed circuit Shelf Life: N/a
Terminal Surface Treatment: Solder Product Name: Microcircuit, digital, uart Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input Terminal Type And Quantity: 48 printed circuit Shelf Life: N/a

Fiig:

A458a0