## NSN 5962-01-468-5076



Hybrid Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-468-5076 **Body Length:** 1.900 inches **Body Width:** 1.000 inches **Body Height:** 0.215 inches **Maximum Power Dissipation Rating:** 2.85 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 2350-01-456-7884/fighting vehicle systems, bradley (bfvs) **Features Provided:** Electrostatic sensitive **Inclosure Configuration:** Dual-in-line **Design Function And Quantity:** 1 multiplexer **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, hybrid, linear, mil-std-1553, bc/rtu/mt, multiplexed terminal Voltage Rating And Type Per Characteristic: -0.3 volts input and 7.0 volts input **Hybrid Technology Type:** Monolithic **Special Features:** Circuit function-mil-std-1553, bc/rt/mt, 12k ram, +5 v transceiver, rt address latch, generic p/n bu-61586x3 **Test Data Document:** 969 06-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 70 printed circuit Shelf Life: N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0