Hybrid Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-468-5076

Bo	dy Length:
1.9	00 inches
Bo	dy Width:
1.0	00 inches
Bo	dy Height:
0.2	15 inches
Ma	kimum Power Dissipation Rating:
2.8	5 watts
Ор	erating Tempurature Range:
-55	0/+125.0 degrees celsius
Sto	rage Tempurature Range:
-65	0/+150.0 degrees celsius
En	Application:
235	0-01-456-7884/fighting vehicle systems, bradley (bfvs)
Fea	tures Provided:
Ele	ctrostatic sensitive
Inc	osure Configuration:
Dua	al-in-line
De	sign Function And Quantity:
1 m	ultiplexer
Ter	minal Surface Treatment:
Sol	der
Pro	duct Name:
Mic	rocircuit, hybrid, linear, mil-std-1553, bc/rtu/mt, multiplexed terminal
Vol	tage Rating And Type Per Characteristic:
-0.3	volts input and 7.0 volts input
Hyl	prid Technology Type:
Мо	nolithic
Spe	ecial Features:
Cire	cuit function-mil-std-1553, bc/rt/mt, 12k ram, +5 v transceiver, rt address latch, generic p/n bu-61586x3
Tes	t Data Document:
969	06-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Ter	minal Type And Quantity:
70	printed circuit
She	elf Life:
N/a	
Uni	t Of Measure:
De	nilitarization:
Yes	- demil/mli
Fiig	r.
A4	8a0