

View Online at <https://aerobasegroup.com/nsn/5962-01-468-5089>

**Maximum Power Dissipation Rating:**

800.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

2350-01-456-7884/fighting vehicle systems, bradley (bfvs)

**Features Provided:**

Monolithic and electrostatic sensitive and 3-state output

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Design Function And Quantity:**

1 transceiver

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, linear, driver/receiver, dual, rs-232, cmos, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

6.0 volts input

**Special Features:**

Circuit function-dual rs-232 driver/receiver, low power, generic p/n max220

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0