NSN 5962-01-469-0821

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-469-0821

Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Depot ita's/aircraft, hercules c-130
Features Provided:
Electrostatic sensitive and 3-state output and monolithic
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Design Function And Quantity:
1 driver, line
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, digital, advanced cmos, octal buffer/line driver, three-state, ttl compatible, monolithic silicon
Voltage Rating And Type Per Characteristic:
-0.5 volts input and 6.0 volts input
Special Features:
Generic p/n 54act244/ttl compatible/non-inverting
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A458a0