## NSN 5962-01-469-2265

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-469-2265

| Overall Height:  |
|--|
| Between 0.060 inches and 0.100 inches  |
| Body Length:   |
| Between 0.342 inches and 0.358 inches  |
| Body Width:  |
| Between 0.342 inches and 0.358 inches  |
| Body Height:   |
| Between 0.050 inches and 0.088 inches  |
| Maximum Power Dissipation Rating:  |
| 1.0 watts  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| C-17a aircraft   |
| Features Provided:   |
| Monolithic   |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Leadless flat pack   |
| Design Function And Quantity:  |
| 1 amplifier, operational, video follower   |
| Terminal Surface Treatment:  |
| Solder   |
| Product Name:  |
| Microcircuit, linear, video operational amplifier, monolithic silicon  |
| Voltage Rating And Type Per Characteristic:  |
| 18.0 volts input   |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc. |
| Terminal Type And Quantity:  |
| 20 leadless  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <u></u>  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |

A458a0