## NSN 5962-01-470-1979

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-470-1979 **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** 0.310 inches **Body Height:** Between 0.133 inches and 0.163 inches **Maximum Power Dissipation Rating:** 1.1 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** B52 cem sau **Features Provided:** Monolithic and wideband and high current and fast settling **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Design Function And Quantity:** 1 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, linear, wideband, high output current, fast settling, operational amplifier, monolithic silicon Voltage Rating And Type Per Characteristic: 5.0 volts input and 15.0 volts input **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli Fiig: