

View Online at <https://aerobasegroup.com/nsn/5962-01-470-2977>

Maximum Power Dissipation Rating:

420.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Aircraft, f16

Features Provided:

Monolithic and electrostatic sensitive and 3-state output and compatible cmos and bipolar

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Bipolar metal-oxide semiconductor

Design Function And Quantity:

1 transceiver

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, advanced bipolar cmos, scan test device with octal bus transceiver with three-state outputs, ttl compatible inputs, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 7.0 volts input

Special Features:

Generic p/n 54abt8245

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0