NSN 5962-01-470-2982

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-470-2982 **Body Length:** 0.358 inches **Body Width:** 0.358 inches **Body Height:** 0.100 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Aircraft, f-16 **Features Provided:** Monolithic and electrostatic sensitive and 3-state output **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Design Function And Quantity:** 1 driver, line and 1 buffer, noninverting **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, digital, fast cmos, noninverting octal buffer/line driver, three-state output, monolithic silicon Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input **Special Features:** Generic p/n 54fct541a **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A458a0