NSN 5962-01-470-3352

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-470-3352

| View Online at https://aerobasegroup.com/nsn/5962-01-470-3352 |
|--|
| Body Length: |
| Between 0.696 inches and 0.713 inches |
| Body Width: |
| Between 0.393 inches and 0.423 inches |
| Body Height: |
| Between 0.092 inches and 0.105 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -40.0/+85.0 degrees celsius |
| Features Provided: |
| Programmable and positive outputs |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Design Function And Quantity: |
| 1 multiplexer, analog |
| Current Rating Per Characteristic: |
| 20.00 milliamperes forward current, nonrepetitive, peak total value absolute |
| Voltage Rating And Type Per Characteristic: |
| 13.0 volts total supply |
| Capitance Rating Per Characteristic: |
| 5.00 input picofarads |
| Terminal Type And Quantity: |
| 28 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |