NSN 5962-01-472-7198

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-472-7198

Maximum Power Dissipation Rating:
1.3 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Aircraft (ac-130h, mc130h, ec-130e, hc130)
Features Provided:
Monolithic and electrostatic sensitive and high speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Design Function And Quantity:
1 amplifier, operational, general purpose
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, linear, high speed, operational amplifier, monolithic silicon
Voltage Rating And Type Per Characteristic:
18.0 volts input
Special Features:
Generic p/n ad846, circuit function-high speed operational amplifier
Test Data Document:
$96906 \hbox{-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)}.$
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0