NSN 5962-01-475-0258



Linear Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-475-0258 **Body Length:** 1.106 millimeters **Body Width:** 1.106 millimeters **Body Height:** 0.160 millimeters **Maximum Power Dissipation Rating:** 1.5 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 1430-01-433-8025/command launch unit **Features Provided:** Electrostatic sensitive and w/schmitt trigger **Inclosure Configuration:** Leaded chip carrier **Criticality Code Justification:** Feat **Design Function And Quantity:** 1 processor, input/output and 1 microprocessor **Terminal Surface Treatment:** Solder **Product Name:** Digital video processor (vp) application specific integrated circuit (asic) Voltage Rating And Type Per Characteristic: -0.5 volts input and 6.0 volts input **Special Features:** Hardness critical item **Nuclear Hardness Critical Feature:** Hardened **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:**

208 gullwing

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-475-0258

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0