NSN 5962-01-475-7560

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-475-7560

Maximum Power Dissipation Rating:
470.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic
Inclosure Material:
Silicon
Inclosure Configuration:
Leadless flat pack
Design Function And Quantity:
1 multiplexer, analog
Current Rating Per Characteristic:
20.00 milliamperes forward current, nonrepetitive, peak total value microamperes
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
44.0 volts total supply
Capitance Rating Per Characteristic:
8.00 input picofarads
Terminal Type And Quantity:
Terminal Type And Quantity: 20 leadless
20 leadless
20 leadless Specification Data:
20 leadless Specification Data: 67268-5962-90635 government standard
20 leadless Specification Data: 67268-5962-90635 government standard Shelf Life:
20 leadless Specification Data: 67268-5962-90635 government standard Shelf Life: N/a
20 leadless Specification Data: 67268-5962-90635 government standard Shelf Life: N/a
20 leadless Specification Data: 67268-5962-90635 government standard Shelf Life: N/a Unit Of Measure:
20 leadless Specification Data: 67268-5962-90635 government standard Shelf Life: N/a Unit Of Measure: Demilitarization:
20 leadless Specification Data: 67268-5962-90635 government standard Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli