NSN 5962-01-475-9286

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-475-9286

Body Le	ngth:
0.460 mil	limeters
Body Wi	dth:
0.460 mil	limeters
Body He	ight:
0.100 mil	limeters
Maximur	n Power Dissipation Rating:
550.5 mil	liwatts
Operatin	g Tempurature Range:
-55.0/+12	5.0 degrees celsius
Storage ⁻	Tempurature Range:
-65.0/+15	0.0 degrees celsius
End App	lication:
Exciter	
Features	Provided:
Electrosta	atic sensitive and monolithic and programmed
Inclosure	e Configuration:
Leadless	flat pack
Product	Name:
Microcirc	uit, programmed prom
Voltage I	Rating And Type Per Characteristic:
4.5 volts	input and 5.5 volts input
Time Rat	ing Per Chacteristic:
25.00 nar	noseconds input
Memory	Device Type:
Eprom	
Special F	Features:
Altered ite	em/uses 5962-88734043x
Test Data	a Document:
96906-mi	I-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal	Type And Quantity:
28 leadle	SS
Shelf Life	9:
N/a	
Unit Of M	leasure:
Demilitar	ization:
Yes - den	nil/mli
Fiig:	
A458a0	