

View Online at <https://aerobasegroup.com/nsn/5962-01-476-0483>

Body Length:

Between 0.540 millimeters and 0.560 millimeters

Body Width:

Between 0.442 millimeters and 0.458 millimeters

Body Height:

Between 0.050 millimeters and 0.080 millimeters

Maximum Power Dissipation Rating:

807.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Exciter

Features Provided:

Electrostatic sensitive and monolithic and high performance and programmable

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Bipolar metal-oxide semiconductor

Design Function And Quantity:

1 buffer, inverting and 1 buffer, noninverting

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, bipolar cmos, programmable skew clock buffer, ttl compatible, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 7.0 volts input

Special Features:

Generic p/n 7b991

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

32 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0