

View Online at <https://aerobasegroup.com/nsn/5962-01-476-2008>

**Body Length:**

Between 0.645 millimeters and 0.665 millimeters

**Body Width:**

Between 0.410 millimeters and 0.422 millimeters

**Body Height:**

Between 0.190 millimeters and 0.200 millimeters

**Maximum Power Dissipation Rating:**

20.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Exciter

**Features Provided:**

Monolithic and electrostatic sensitive and adjustable and burn in

**Inclosure Material:**

Glass

**Inclosure Configuration:**

Can

**Design Function And Quantity:**

1 regulator, voltage

**Case Outline Source And Designator:**

To-257 joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, linear, adjustable (-1.2 to -37v) negative voltage regulator, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

40.0 volts input

**Special Features:**

Generic p/n lm137a/uses m38510/11803bux

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0