

View Online at <https://aerobasegroup.com/nsn/5962-01-476-2014>

**Body Length:**

0.385 millimeters

**Body Width:**

Between 0.235 millimeters and 0.260 millimeters

**Maximum Power Dissipation Rating:**

88.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Exciter

**Features Provided:**

Electrostatic sensitive and monolithic and schottky

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leaded chip carrier

**Output Logic Form:**

Transistor-transistor logic

**Design Function And Quantity:**

1 flip-flop, d-type

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, advanced schottky ttl, dual d-type flip-flop, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

-0.5 volts input and 7.0 volts input

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0