

View Online at <https://aerobasegroup.com/nsn/5962-01-476-2473>

Body Length:

0.358 inches

Body Width:

0.358 inches

Body Height:

0.100 inches

Maximum Power Dissipation Rating:

66.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Universal exciter upgrade

Features Provided:

Schottky and monolithic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

3 input

Design Function And Quantity:

1 gate, nand

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital-bipolar, advanced schottky ttl, 3-input nor gates, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 7.0 volts input

Special Features:

Shall meet requirements of smd 5962-89510012x; and device shall be capable of meeting an esd level of class 2

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0