

View Online at <https://aerobasegroup.com/nsn/5962-01-476-2747>

**Body Length:**

0.358 inches

**Body Width:**

0.358 inches

**Body Height:**

0.100 inches

**Maximum Power Dissipation Rating:**

303.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Universal exciter upgrade

**Features Provided:**

Bipolar and schottky and synchronous and monolithic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Transistor-transistor logic

**Design Function And Quantity:**

1 counter, binary

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, bipolar, advanced schottky ttl, synchronous 4-bit binary counter, synchronous reset, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Special Features:**

Shall meet requirements of mil-m-38510/34302b2x; and device shall be capable of meeting an esd level of a class 2

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0