## NSN 5962-01-476-3666

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-476-3666 **Body Length:** 1.250 inches **Body Width:** 0.950 inches **Body Height:** 0.450 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -55.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Universal exciter upgrade **Features Provided:** Hybrid **Inclosure Configuration:** Flat pack **Design Function And Quantity:** 1 switch, analog, single pole double throw **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, linear, sp2t 20 to 2000 mhz rf switch, hybrid Voltage Rating And Type Per Characteristic: 7.0 volts input **Special Features:** Device shall meet requirements of military specifications mil-prf-38534 **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 4 case Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli Fiig:

Mil-prf-38534 spec.

Mil-std (military Standard):

A458a0