

View Online at <https://aerobasegroup.com/nsn/5962-01-476-3699>

**Body Length:**

0.300 inches

**Body Width:**

0.270 inches

**Body Height:**

0.075 inches

**Operating Temperature Range:**

-54.0/+85.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Universal exciter upgrade

**Features Provided:**

Monolithic

**Inclosure Configuration:**

Flat pack

**Design Function And Quantity:**

1 switch, driver

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, linear-gaas spdt fet mmic switch with integral driver, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

7.0 volts input

**Special Features:**

Device shall meet requirements for class b microcircuits in accordance with military specifications mil-prf-38534; and selection criteria shall be performed per paragraph 3.2.1 (terminal connctions) and the electrical performance characteristics listed in table i

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

10 gullwing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0

**Mil-std (military Standard):**

Mil-prf-38534 spec.