## NSN 5962-01-480-7182

Digital Microcircuit - Page 1 of 1



1-480-7182

| View Online at https://aerobasegroup.com/nsn/5962-0     |
|---|
| Operating Tempurature Range:                            |
| -40.0/+85.0 degrees celsius                             |
| Storage Tempurature Range:                              |
| -65.0/+150.0 degrees celsius                            |
| End Application:  |
| Engine, aircraft f-100-pw-22 (f-15e, f-16c/d)           |
| Features Provided:                                      |
| Electrostatic sensitive                                 |
| Inclosure Configuration:                                |
| Leaded chip carrier                                     |
| Output Logic Form:                                      |
| Complementary-metal oxide-semiconductor logic           |
| Design Function And Quantity:                           |
| 4 receiver, line differential                           |
| Product Name:   |
| Microcircuit, cmos-quarduple differential line receiver |
| Voltage Rating And Type Per Characteristic:             |
| -0.5 volts input and 7.0 volts input                    |
| Special Features:                                       |
| Generic p/n 26c32                                       |
| Terminal Type And Quantity:                             |
| 16 gullwing   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:                                       |
| Yes - demil/mli   |
| Fiig:   |

A458a0