

View Online at <https://aerobasegroup.com/nsn/5962-01-483-1896>

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Cp-2237/sps-4, oliver perry class ffg

Features Provided:

Electrostatic sensitive and monolithic and ultraviolet erasable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital, uve prom

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 7.0 volts input

Time Rating Per Characteristic:

65.00 nanoseconds af output megawatts

Memory Device Type:

Eprom

Special Features:

Altered item made from 5962-8953701ya/burn file p/n bfg553506-217

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0