## NSN 5962-01-484-6554

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-484-6554

| Maximum Power Dissipation Rating:  |
|--|
| 1.0 watts  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| Aircraft, awacs, e-3a  |
| Features Provided:   |
| Monolithic and electrostatic sensitive and programmed  |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Product Name:  |
| Microcircuit, programmed   |
| Voltage Rating And Type Per Characteristic:  |
| -0.5 volts input and 7.0 volts input   |
| Time Rating Per Chacteristic:  |
| 25.00 nanoseconds access   |
| Memory Device Type:  |
| Eeprom   |
| Special Features:  |
| Altered item/uses smd 5962-8751511lx   |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:  |
| 24 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |
|  |