NSN 5962-01-485-0506

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-485-0506

| view Online at https://aerobasegroup.com/nsn/5962-01-465-0506 |
|--|
| Body Length: |
| Between 0.697 inches and 0.713 inches |
| Body Width: |
| Between 0.291 inches and 0.300 inches |
| Body Height: |
| Between 0.092 inches and 0.105 inches |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Air combat maneuvering instrumentation |
| Features Provided: |
| Synchronous and low power and high speed |
| Inclosure Configuration: |
| Dual-in-line Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Design Function And Quantity: |
| 1 amplifier, radio frequency |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 28 gullwing |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |
| Fila: |