

View Online at <https://aerobasegroup.com/nsn/5962-01-485-8406>

**Maximum Power Dissipation Rating:**

140.00 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

1055-01-329-6826/multiple launch rocket system (mlrs)

**Features Provided:**

Electrostatic sensitive and monolithic and low power and schottky

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Design Function And Quantity:**

1 encoder, priority, ten to four line

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, low power schottky ttl, 10-line-to-4-line priority encoder, monolithic silicon

**Voltage Rating And Type Per Characteristic:**

7.0 volts total supply

**Special Features:**

Generic p/n 54ls147

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0