NSN 5962-01-485-8722

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-485-8722

| Maximum Power Dissipation Rating: |
|--|
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+155.0 degrees celsius |
| End Application: |
| Seawolf class ssn |
| Features Provided: |
| Monolithic |
| Inclosure Configuration: |
| Leadless flat pack |
| Product Name: |
| Microcircuits, memory, digital, cmos, 4kx9 fifo, monolithic silicon |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 40.00 nanoseconds access |
| Memory Device Type: |
| First-in first-out |
| Test Data Document: |
| $96906 \hbox{-mil-std-}883 \ standard \ (includes \ industry \ or \ association \ standards, \ individual \ manufactureer \ standards, \ etc.).$ |
| Terminal Type And Quantity: |
| 32 leadless |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |