NSN 5962-01-493-5903

Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-493-5903

Maximum Power Dissipation Rating: 1000.0 milliwatts Operating Tempurature Range: -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Electrostatic sensitive and monolithic and programmable and synchronous and bipolar and low power and high specific sp	∍ed
Operating Tempurature Range: -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Electrostatic sensitive and monolithic and programmable and synchronous and bipolar and low power and high specific specification:	∍ed
-40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Electrostatic sensitive and monolithic and programmable and synchronous and bipolar and low power and high specific	∍ed
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Electrostatic sensitive and monolithic and programmable and synchronous and bipolar and low power and high specific configuration:	∍ed
-65.0/+150.0 degrees celsius Features Provided: Electrostatic sensitive and monolithic and programmable and synchronous and bipolar and low power and high specific configuration:	∍ed
Features Provided: Electrostatic sensitive and monolithic and programmable and synchronous and bipolar and low power and high specific configuration:	∍ed
Electrostatic sensitive and monolithic and programmable and synchronous and bipolar and low power and high spe Inclosure Configuration:	∍ed
Inclosure Configuration:	ed
Dual-in-line	
Output Logic Form:	
Complementary-metal oxide-semiconductor logic	
Design Function And Quantity:	
1 converter, digital to analog	
Terminal Surface Treatment:	
Solder	
Product Name:	
Lc2mos complete, dual 12 bit mdacs	
Voltage Rating And Type Per Characteristic:	
-0.3 volts input and 17.0 volts input	
Terminal Type And Quantity:	
24 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	