NSN 5962-01-496-5281

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-496-5281

Body	Lon	ath.
DOUV	Len	atn.

Between 12.65 millimeters and 12.95 millimeters

Body Width:

Between 7.40 millimeters and 7.60 millimeters

Body Height:

Between 2.35 millimeters and 2.65 millimeters

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Tempurature Range:

-55.0/+150.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Elect test, equipment - gpete/ protrack 1, m

Features Provided:

Electrostatic sensitive and monolithic and high performance and 3-state output and inverted output

Inclosure Configuration:

Dual-in-line

Design Function And Quantity:

1 receiver, line

Terminal Surface Treatment:

Solder

Product Name:

Octal 3-state inverting buffer/line driver/ line receiver

Voltage Rating And Type Per Characteristic:

-0.5 volts input and 7.0 volts input

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0