

View Online at <https://aerobasegroup.com/nsn/5962-01-497-7775>

**Maximum Power Dissipation Rating:**

300.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

1430-01-184-6768/radar set, semitrailer mounted

**Features Provided:**

Ultraviolet erasable and electrostatic sensitive

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Design Function And Quantity:**

1 memory, electrically erasable programmable rom

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital - memory, cmos, 16k x 8 bit uveprom

**Voltage Rating And Type Per Characteristic:**

-0.6 volts input and 6.25 volts input

**Time Rating Per Characteristic:**

200.00 nanoseconds access

**Special Features:**

Generic p/n 27c128/built on requirements of smd 5962-87661 type 05

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

28 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0