

View Online at <https://aerobasegroup.com/nsn/5962-01-497-7775>

Maximum Power Dissipation Rating:

300.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

1430-01-184-6768/radar set, semitrailer mounted

Features Provided:

Ultraviolet erasable and electrostatic sensitive

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Design Function And Quantity:

1 memory, electrically erasable programmable rom

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, digital - memory, cmos, 16k x 8 bit uveprom

Voltage Rating And Type Per Characteristic:

-0.6 volts input and 6.25 volts input

Time Rating Per Characteristic:

200.00 nanoseconds access

Special Features:

Generic p/n 27c128/built on requirements of smd 5962-87661 type 05

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0